
TECHNICAL DATA SHEET

MACH1 TRUCKY 30 rim

VELOX L'UNIVERS DU VÉLO
reparermaroue.fr

Sturdy and tubeless ready, tyres up to 2.8". e-MTB, longtail, trailer.





RIM CROSS-SECTION

The Mach1 Trucky 30 rim is a sturdy, tubeless ready rim in 30C, suited to wide tyres of up to 2.8 inches. Perfect for intensive use, whether in an urban or a sporting setting, it is ideally suited to e-MTBs, longtail bikes and trailers. Its shape ensures excellent tyre retention, even at low pressure, and it supports a maximum load of 250 kg in cargo use, thereby guaranteeing safety and reliability.

- Aluminium 6063 T6
- Double wall with eyelets, disc brake
- Tubeless ready
- Made in France

USE

MTB / XC | E-TREKKING / E-CITY | E-MTB | CARGO / BOX BIKE | LONGTAIL

MAXIMUM LOAD RATINGS

USE	AXLE LOAD	MAX LOAD
Cargo / box bike	150 kg	250 kg
Longtail	150 kg	215 kg
e-MTB	85 kg	150 kg
e-City / e-Trekking	120 kg	180 kg

SPECIFICATIONS COMMON TO ALL DIAMETERS

Wall	Double	Tyre widths (inches)	1.85–2.80"
Eyelets	Yes	Tubeless ready	Yes
Internal width	30C	Material	Aluminium 6063 T6
External width	35 mm	Origin	Made in France
Height	18 mm	Manufacturer reference	ML10
Brake type	Disc	Colours	Black
Tyre widths	47–71 mm		

SPECIFICATIONS BY DIAMETER

Diameter	20"	24"	26"	27.5"	28/29"
ETRTO	406 × 30C	507 × 30C	559 × 30C	584 × 30C	622 × 30C
ERD	386 mm	488 mm	539 mm	564 mm	603 mm
Weight	450 g	560 g	615 g	640 g	685 g
Hole counts offered	28T · 32T · 36T	32T · 36T	32T · 36T	32T · 36T	32T · 36T
Sheet on the website	Open the sheet	Open the sheet	Open the sheet	Open the sheet	Open the sheet

TYRE PRESSURE

Tyre widths (mm)	47 – 55	57 – 62	64 – 71
Tyre widths (inches)	1.85 – 2.1"	2.2 – 2.45"	2.5 – 2.8"
Pressure (bar)	7.5 – 6	6 – 5.5	5.5 – 4.5

Source: Mach1