TUBASTI® TUBULAR GLUE

Instructions for use

Glue a tubular onto a carbon or aluminium rim.

VELOX®
L'UNIVERS DU VÉLO



Tubasti® in a tube

25 g tube for 1 tubular, carbon and alu

Single, or in packs of 10 or 30

R421K00 · R421P00 · R421J00



Tubasti® in a pot

240 ml pot, carbon and alu rims

Use within a month of opening

R044O00




1 Stretch the tyre

24 h before gluing, fit the tubular dry on a wheel and inflate it to the maximum: it stretches and takes shape.




2 Clean the rim

Degrease it with Velox Glue and Sealant Remover, leave it to act, wipe. Rim already glued: remove any old glue that comes away.




3 Glue the rim

Clean, solvent-free brush: a thin coat in the rim bed, right up to the edges. New rim: 2 coats, the 1st dry before the 2nd.



4 Glue the tubular

Same thin, even coat on the base tape, without going over onto the sidewalls. If in doubt, more rather than less.




5 Let it dry

Wait 10 minutes for the glue to become tacky, on the rim and on the tubular. Close the tube or pot tightly: the glue dries in the air.




6 Fit the tubular

Fit the deflated tubular starting at the valve, stretching it in both directions at once, round to the opposite point.



7 Centre it

Inflate it slightly and centre it while turning the wheel: the base tape must show equally on both sides.



8 Inflate to 8 bar

8 bar, i.e. 115 psi. Then let the glue dry for 24 h before riding.

After fitting

⚠ Check, after the 24 h drying time: with the tubular deflated, push it sideways; it must not come unstuck. **If in doubt, ask a professional.**

- Before every ride, check the bond and the pressure.
- To remove: peel the tubular off by hand, never with a screwdriver. To reglue: start again from step 2.

Good to know

- **Tubasti®**: tubulars of all brands, carbon and aluminium rims.
- Never exceed the tubular's maximum pressure.
- Glue on the braking surface: wipe it off while fresh with the Velox remover.
- Once opened, use the glue within a month. **If in the slightest doubt, do not use it.**



DANGER

In compliance with EC regulation No. 1272/2008 and its amendments. Contains: EC 205-500-4 ETHYL ACETATE; EC 927-510-4 HYDROCARBONS, C7, N-ALKANES, ISOALKANES, CYCLICS; EC 200-662-2 ACETONE; EC 232-475-7 ROSIN, COLOPHONY. Highly flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing mist/vapours. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER/doctor/if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Store in a well-ventilated place. Keep cool. Dispose of contents/container at a disposal facility in accordance with local regulations. UFI: 8800-30JY-U001-50FQ.

Établissements Velox · 13, rue de la Peltière · 35130 La Guerche-de-Bretagne · France · +33 (0)2 99 75 17 81 · velox@velox.fr

Emergency telephone number (ORFILA): +33 (0)1 45 42 59 59

Tubular glues and Jantex: the full range on velox.fr.