JANTEX 14 AND JANTEX 76

Fitting instructions

Fit a tubular with double-sided tape, with no glue and no drying time.

VELOX
L'UNIVERS DU VÉLO



Jantex 76

Aluminium rims
18 mm tape
4.15 m roll for 2 wheels



Jantex 14

Carbon and aluminium rims
Withstands up to 300 °C
18 or 21 mm · 1 wheel (2 m) or 2 wheels



1 Stretch the tyre

At least 24 h before gluing, fit the tubular on a wheel and inflate it to its maximum pressure: it stretches and takes shape.




2 Clean the rim

Clean rim, free of glue and grease: Velox Glue and Sealant Remover, leave it to act, wipe. Let it dry before applying the Jantex.



3 Apply the tape

Stick the Jantex in the centre of the rim: start at the valve and go all the way round back to the valve, without covering it.




4 Free the liner

Peel back a few centimetres of liner at each end, and let them hang down on either side of the rim.



5 Fit the tubular

Fit the deflated tubular starting at the valve, stretching it in both directions at once, round to the opposite point.




6 Centre it

Inflate it slightly and centre it on the rim. As long as the liner is in place, the tubular slides without sticking.



7 Remove the liner

Holding the tubular firmly, gently pull the red liner out to the point opposite the valve, on both sides: the tubular sticks as you go.



8 Inflate, ride

Inflate to the pressure recommended by the tubular manufacturer. No drying time: you can ride straight away.

After fitting

⚠ Check: with the tubular deflated, push it sideways; it must not come unstuck. **If in doubt, ask a professional.**

- Before every ride, check the bond and the pressure.
- To remove: peel the tubular off by hand, never with a screwdriver. To refit: use new tape.

Good to know

- **Jantex 76**: aluminium rims. **Jantex 14**: carbon or aluminium.
- 18 mm for 19 to 23 mm tubulars, 21 mm for 21 to 25 mm.
- Fitted without tools, on 650 and 700 wheels.
- No sandpaper: it scratches the rim and reduces the bonding surface.

You will need

- Velox Glue and Sealant Remover and a clean cloth
- A craft knife or scissors
- A pump with a pressure gauge

Velox part numbers

REF.	PRODUCT	TAPE	TUBULARS	ROLL
R040V00203	Jantex 76	18 mm	19 to 23 mm	2 wheels · 4.15 m
R040S00	Jantex 76, pack of 5	18 mm	19 to 23 mm	2 wheels · 4.15 m
R040CS01	Jantex 14	18 mm	19 to 23 mm	1 wheel · 2 m
R040CS00	Jantex 14	18 mm	19 to 23 mm	2 wheels · 4.15 m
R040CS02	Jantex 14	21 mm	21 to 25 mm	1 wheel · 2 m
E400C00-REM	Glue and sealant remover, 400 ml aerosol			

Jantex and tubular glues: the full range on velox.fr.

Établissements Velox · 13, rue de la Peltière · 35130 La Guerche-de-Bretagne · France · +33 (0)2 99 75 17 81 · velox@velox.fr